SAFETY DATA SHEET

1. Identification

Product number 1000007123

Product identifier 18 OZ KOIL KLEEN LB 24PK (2-12PK) Company information MATRIX MAINTENANCE SUPPLY LLC

3861 SYLON BLVD.

Mt. Laurel, NJ 08054 United States

General Assistance 609-267-5455 Company phone

1-866-836-8855 **Emergency telephone US Emergency telephone outside**

1-952-852-4646

US

01 Version # Recommended use Cleaner **Recommended restrictions** None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

If exposed or concerned: Get medical advice/attention. Response

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Sodium Nitrite		7632-00-0	0.1 - 1
Other components below reportable levels			90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK)

Product #: 1000007123 Version #: 01 Issue date: 02-15-2016

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

Direct contact with eyes may cause temporary irritation.

delayed

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Not available.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

and precautions for firefighters Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

Extremely flammable aerosol. General fire hazards

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK)

US. ACGIH Threshold Limit Values

Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che Components	emical Hazards Type	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 80 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

Not available.

Not available.

Not available.

Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.898 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
Sodium Nitrite (CAS 7632-0	00-0)	
<u>Acute</u>		
Oral		
LD50	Rat	180 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK)

Product #: 1000007123 Version #: 01 Issue date: 02-15-2016

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not likely, due to the form of the product.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Sodium Nitrite (CAS 7	(632-00-0)		
Aquatic			
Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis)	16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0.15 - 0.25 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Butane 2.89 Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK)

14. Transport information

DOT

UN1950 **UN** number

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 306 **Packaging exceptions** Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number

Aerosols, flammable **UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. **Packing group**

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No. **EmS** F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

LTD QTY **Packaging Exceptions** Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK) Product #: 1000007123 Version #: 01 Issue date: 02-15-2016



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Sodium Nitrite (CAS 7632-00-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Nο

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Sodium Nitrite7632-00-00.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Nitrite (CAS 7632-00-0)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Sodium Nitrite (CAS 7632-00-0)

Product name: 18 OZ KOIL KLEEN LB 24PK (2-12PK)

Product #: 1000007123 Version #: 01 Issue date: 02-15-2016

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Sodium Nitrite (CAS 7632-00-0)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6) Sodium Nitrite (CAS 7632-00-0)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

02-15-2016 Issue date

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

> information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product and Company Identification: Alternate Trade Names **Revision information**

Hazard(s) identification: Response

Product #: 1000007123 Version #: 01 Issue date: 02-15-2016

Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).