# SAFETY DATA SHEET

#### 1. Identification

Product number	100000525
Product identifier	Matrix Steel Shine
Company information	MATRIX MAINTENANCE SUPPLY LLC 3861 SYLON BLVD. Mt. Laurel, NJ 08054 United States
Company phone	General Assistance 609-267-5455
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	CLEANER
Recommended restrictions	None known.

## 2. Hazard(s) identification

Physical hazards
Health hazards
OSHA defined hazards

#### Label elements

Flammable aerosols Aspiration hazard Not classified.

Category 1 Category 1



	• • • • • • • • • • • • • • • • • • •	
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.	
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.	
Storage	Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
Hazard(s) not otherwise classified (HNOC)	Combustible.	
Supplemental information	None.	

## 3. Composition/information on ingredients

**Mixtures** 

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
Distillates (petroleum), Hydrotreated Light		64742-47-8	10 - 20
Propane		74-98-6	2.5 - 10
Other components below repo	ortable levels		60 - 80

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>o</b> in it i	

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol. Combustible.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage,	Level 1 Aerosol.
including any incompatibilities	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Туре	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Lim		
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
US. NIOSH: Pocket Guide	to Chemical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
ological limit values	No biological exposure limits noted	for the ingredient(s).
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
ividual protection measure	es, such as personal protective equip	ment
Eye/face protection	Face shield is recommended. Wear	r safety glasses with side shields (or goggles).
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.	
Other	Wear suitable protective clothing.	
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
neral hygiene nsiderations		observe good personal hygiene measures, such as washing ore eating, drinking, and/or smoking. Routinely wash work

## 9. Physical and chemical properties

Appearance		
Physical state	Gas.	
Form	Aerosol.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	212 °F (100 °C) estimated	
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	

Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	570.2 °F (299 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.823 estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and	Aspiration may cause pulmonary edema and pneumonitis.

toxicological characteristics

## Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.	
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Distillates (petroleum), Hy	drotreated Light (CAS 64742-47-8)	
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours

	Species		Test Results	
			> 4.6 mg/l, 4 Hours	
Oral				
LD50	Rat		> 5000 mg/kg	
Propane (CAS 74-98-6)				
<u>Acute</u>				
Inhalation				
LC50	Mouse		1237 mg/l, 120 Minutes	
			52 %, 120 Minutes	
	Rat		1355 mg/l	
			658 mg/l/4h	
* Estimates for product may h	e based on a	dditional component data not shown.		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.			
Respiratory or skin sensitization	n			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This produ	ct is not considered to be a carcinogen	by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall	Evaluation o	f Carcinogenicity		
OSHA Specifically Regulate Not regulated. US. National Toxicology Pro Not listed.				
Reproductive toxicity	This produ	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	May be fatal if swallowed and enters airways.			
12. Ecological information	า			
Ecotoxicity	The produc		azardous. However, this does not exclude the harmful or damaging effect on the environment.	
		Species	Test Results	
Components				
Components Distillates (petroleum), Hydro	treated Light	(CAS 64742-47-8)		
	treated Light	(CAS 64742-47-8)		
Distillates (petroleum), Hydro	treated Light LC50	(CAS 64742-47-8) Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours	
Distillates (petroleum), Hydro <b>Aquatic</b> Fish	LC50 be based on a	Rainbow trout, donaldson trout		
Distillates (petroleum), Hydro <b>Aquatic</b> Fish * Estimates for product may b	LC50 be based on a	Rainbow trout,donaldson trout (Oncorhynchus mykiss) dditional component data not shown.		
Distillates (petroleum), Hydro Aquatic Fish * Estimates for product may b Persistence and degradability Bioaccumulative potential Partition coefficient n-octar	LC50 be based on a No data is	Rainbow trout,donaldson trout (Oncorhynchus mykiss) dditional component data not shown. available on the degradability of this pro		
Distillates (petroleum), Hydro Aquatic Fish * Estimates for product may b Persistence and degradability Bioaccumulative potential Partition coefficient n-octar Butane	LC50 be based on a No data is	Rainbow trout,donaldson trout (Oncorhynchus mykiss) dditional component data not shown. available on the degradability of this pro og Kow) 2.89		
Distillates (petroleum), Hydro Aquatic Fish * Estimates for product may b Persistence and degradability Bioaccumulative potential Partition coefficient n-octar Butane Propane	LC50 be based on a No data is <b>nol / water (lo</b>	Rainbow trout,donaldson trout (Oncorhynchus mykiss) dditional component data not shown. available on the degradability of this pro og Kow) 2.89 2.36		
Distillates (petroleum), Hydro Aquatic Fish * Estimates for product may b Persistence and degradability Bioaccumulative potential Partition coefficient n-octar Butane	LC50 be based on a No data is <b>nol / water (lo</b> No data av	Rainbow trout,donaldson trout (Oncorhynchus mykiss) dditional component data not shown. available on the degradability of this pro og Kow) 2.89 2.36 ailable.		

#### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## 14. Transport information

#### DOT

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, flammable, (each not exceeding 1 L capacity)
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### ΙΑΤΑ

101	~	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.
	Packaging Exceptions	LTD QTY
IMC	G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	
	Marine pollutant	No.
	EmS	F-D, S-U
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Packaging ExceptionsLTD QTYTransport in bulk according to<br/>Annex II of MARPOL 73/78 and<br/>the IBC CodeNot applicable.



15. Regulatory informatio	n	
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)		
Not regulated.		
CERCLA Hazardous Substance List (40 CFR 302.4)		
Not listed.		
SARA 304 Emergency relea	ase notification	
Not regulated.	ed Substances (29 CFR 1910.1001-1050)	
Not regulated.	eu Substances (29 CFN 1910.1001-1050)	
Superfund Amendments and Reauthorization Act of 1986 (SARA)		
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazar	dous substance	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated.		
Clean Air Act (CAA) Section	n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Butane (CAS 106-97-8) Propane (CAS 74-98-6)		
Safe Drinking Water Act (SDWA)	Not regulated.	

#### **US state regulations**

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)

**US. Massachusetts RTK - Substance List** 

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

## US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

Issue date Version #	12-04-2018 01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
<b>Revision information</b>	Product and Company Identification: Alternate Trade Names